



RIG 34 - TELESCOPIC DOUBLE

Depth Capacity (TVD) : 3,600 m Rig Loads : 15 (+ Rentals & Pipe)

MAST

Mast Type	<i>Telescopic Double</i>	Drill Line Size (mm)	<i>28.6</i>
Mast MFG	<i>Mastco</i>	Number of Lines	<i>10</i>
Static Hook Load (daN)	<i>172,800</i>	3:1 Capacity (daN)	<i>157,000</i>
Mast Clear Height (m)	<i>32.0</i>	2:1 Capacity (daN)	<i>235,000</i>

Drill Line API Specification for EIPS 6 x19 is:

3 : 1 Safety factor drilling; 2 : 1 Safety factor running casing or stuck pipe.

SUBSTRUCTURE

Substructure Type	<i>One Piece, Step-down</i>	Racking Capacity (101.6 mm)	<i>4,400 m</i>
Substructure MFG	<i>Mastco</i>	Racking Capacity (114.3 mm)	<i>4,400 m (w/DS40 TJ)</i>
Setback Capacity (daN)	<i>122,000</i>	Racking Capacity (127.0 mm)	<i>3,300 m</i>
BOP-Sub Clr. w/ Pony (m)	<i>3.96</i>	Rotary Table MFG	<i>SJ Petro</i>
Floor Height w/ Pony (m)	<i>4.72</i>	Rotary Table Capacity (daN)	<i>172,800</i>
Pony Sub Height (m)	<i>Pontoon</i>	Rotary Table Size	<i>17.5"</i>

Racking Capacity does NOT take into account the added weights of HWDP or drill collars.

DRAWWORKS (MECHANICAL)

Drawworks MFG	<i>TSM</i>	Drawworks Drive	<i>Detroit Series 60</i>
Drawworks Model	<i>TSM 7000</i>	Drive Rating (hp)	<i>600</i>
Single Line Pull (daN)	<i>21,500</i>	Auxiliary Brake	<i>Eaton 324WCBD</i>
Rated Power (hp)	<i>750</i>	Transmission	<i>Allison 6061</i>

OVERHEAD EQUIPMENT

Block Model	<i>McKissick 250T</i>	Block Capacity (ton)	<i>250</i>
Becket Model	<i>McKissick 250T</i>	Becket Capacity (ton)	<i>250</i>
Topdrive	<i>Tesco 250-HMI-475</i>	Make-Up Torque (ft-lb)	<i>21,000</i>
Continuous Torque (ft-lb)	<i>21,000</i>	Break Out Torque (ft-lb)	<i>23,500</i>

HIGH PRESSURE CIRCULATING SYSTEM

System Pressure (psi)	<i>5,000</i>
-----------------------	--------------

MUD PUMP 1

Pump MFG & Model	<i>TSC Offshore WF-1300</i>	Mud Pump Drive	<i>Cummins QST30</i>
Pump Rated Power (hp)	<i>1,300</i>	Pump Drive Rating (hp)	<i>1,350</i>
Pump Stroke Length	<i>11"</i>	Gear Box Ratio	<i>2 : 1 & 3 : 1</i>
Gear Box MFG	<i>Rouse Industries</i>	Gear Box Rated Power (hp)	<i>1,350</i>

MUD SYSTEM

Total Volume (m ³)	<i>89</i>	# of Mud Tanks	<i>1</i>
Active Volume (m ³)	<i>71</i>	# of Compartments	<i>3 + 1 Trip + 1 Pill</i>
Trip Tank Volume (m ³)	<i>4.7</i>	Pill Tank Volume (m ³)	<i>4.9</i>
Agitators Power (qty)	<i>5.6 kW (3)</i>	Mixing Hopper (qty)	<i>Conventional (1)</i>
Centrifugal Pump Quantity	<i>3</i>	Centrifugal Pump Size (mm)	<i>152 x 127 x 279</i>
Shale Shaker (qty)	<i>Brandt King Cobra (2)</i>	Degasser Size (mm)	<i>914</i>



BOPs (NACE)

Annular	<i>Townsend T84</i>	Pressure Rating & Size	<i>3,000 psi, 9"</i>
Ram #1	<i>Townsend T88 - Single</i>	Pressure Rating & Size	<i>3,000 psi, 9"</i>
Ram #2	<i>Townsend T88 - Single</i>	Pressure Rating & Size	<i>3,000 psi, 9"</i>

ACCUMULATOR

Accumulator MFG	<i>ABB Offshore Sys.</i>	Operating Pressure (psi)	<i>3,000</i>
Accumulator Volume (l)	<i>303</i>	# of Stations	<i>5</i>

CHOKE MANIFOLD (NACE)

Type	<i>Single Gut</i>	Pressure Rating (psi)	<i>3,000</i>
Size	<i>2-1/16"</i>		

GENERATOR SETS

Generator MFG	<i>Stamford</i>	Engine MFG	<i>Detroit</i>
Generator Model (qty)	<i>HCI434F1L (2)</i>	Engine Model (qty)	<i>Series 60 (2)</i>
Prime Rating (kW)	<i>350 (Each)</i>	Voltage (V)	<i>208 / 480</i>

MISCELLANEOUS EQUIPMENT

Fuel Tank Capacity (m ³)	<i>16 (Total)</i>	Pipe Tub Type	<i>Conventional</i>
# of Fuel Tanks	<i>1</i>	Catwalk	<i>Hydraulic</i>
Water Tank Capacity (m ³)	<i>60 (Total)</i>	Catwalk Clear Height	<i>N/A</i>
# of Water Tanks	<i>1</i>	Catwalk Clear Width	<i>N/A</i>

RENTAL



Boiler MFG	<i>Williams & Davis Boilers</i>	Boiler Rating (hp)	<i>100</i>
Flare Tank Skid	<i>As Required</i>	Loader	<i>As Required</i>

Rental equipment are not included in the rig load count.

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.

RIG 34 – TELESCOPIC DOUBLE

Depth Capacity (TVD): 3,600 m / 11,800'



Quantity of pipe tubs in the layout may vary due to customer requirements.